

Material Safety Data Sheet

FAKKT-G133 Grease

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: FAKKT-G133 Grease
General Use: Lubricating Grease
Manufacturer: Shenzhen Hecheng Lube Material Co.,Ltd.
Tel:0755-28167635
Fax:0755-28167603

HMIS
H 1
F 0
R 0
PPE†
†Sec. 8

Section 2 - Composition / Information on Ingredients

Color, appearance: brown, smooth

Chemical name	% wt or %	CAS NO.
technical white oil	70-80%	8012-95-1
Polyolefin	10-15%	68037-01-4
Polyurea	10-15%	43136-14-7
Additive	1-5%	---

Product formulation is Proprietary
NO ingredients are known to be hazardous under normal usage.

Section 3 - Hazards Identification

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Summary of risks: There is no experience with overexposure. Prolonged or repeated skin or eye contact may cause irritation. Inhalation of vapor or oil mist from material at high temperatures may irritate respiratory passages. Limit for airborne concentration of oil mist in air is 5mg/m³ per OSHA 29 CFR 1910.1000. **Exercise ordinary, common-sense measures of industrial hygiene when using this product.**

Potential Health Effects

Primary Entry Routes: Skin, eyes, inhalation at high temperatures (over 250°C).
Target Organs: Skin, eyes, respiratory passages at high temperatures (over 250°C).
Acute Effects: Possible skin and eye irritation. Possible respiratory passage irritation at high temperatures (over 250°C).
Carcinogenicity: IARC, NTP, and OSHA , its ingredients as carcinogens.
Medical Conditions Aggravated by Long-Term Exposure: None known.
Chronic Effects: None known.

Section 4 - First Aid Measures

Inhalation: Move to fresh air and refer to a physician for treatment.
Eye Contact: Wash thoroughly; contact physician if irritation persists.
Skin Contact: Wash thoroughly with soap and water.
Ingestion: Not expected to be a problem. However, if ingested, immediately give 1 to 2 glasses of water and call a physician. Do not induce vomiting.
After first aid, get appropriate in-plant, paramedic, or community medical support.
Special Precautions/Procedures: Avoid contamination of cigarettes or other tobacco products.

Section 5 - Fire-Fighting Measures

Flash Point: over 280°C
Flash Point Method: COC
LEL: N/A
UEL: N/A
Extinguishing Media: CO₂, Foam, Dry Chemical, Water Spray
Unusual Fire or Explosion Hazards: None
Hazardous Combustion Products: Carbon Monoxide and small amount of other toxic fumes.



FAKKT-G133

Fire-Fighting Instructions: Avoid smoke inhalation. Water or foam may cause frothing. Do not release runoff from fire control methods to sewers or waterways.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full facepiece operated in pressure-demand or positive-pressure mode.

Section 6 - Accidental Release Measures

Spill /Leak Procedures: Wipe or scrape up grease spillage and place it in a container for disposal.

Containment: Do not release into sewers or waterways.

Cleanup: Wash walking surfaces thoroughly with detergent and water to reduce slipping hazard.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120). Consult applicable state and local regulations.

Section 7 - Handling and Storage

Handling Precautions: Exercise ordinary care in handling industrial lubricants. No special handling precautions are necessary. Avoid contamination of cigarettes or other tobacco products. Wash hands thoroughly before eating or smoking. Users should be alert to the possibility that very small percentages of the population may display unexpected allergic reactions to otherwise innocuous industrial lubricants and raw materials.

Storage Requirements: Do not store in open or unlabeled containers. Store away from strong oxidizing agents or combustible material.

Regulatory Requirements: None

Section 8 - Exposure Controls / Personal Protection

Ventilation: No special requirements under ordinary conditions of use with adequate ventilation.

Respiratory Protection: Not required unless oil mist, smoke or vapors are generated at high temperatures.

Protective Clothing/Equipment: Wear chemically protective gloves, and aprons to prevent prolonged or repeated skin contact. Wear protective eyeglasses or chemical safety goggles, per OSHA eye- and face-protection regulations (29 CFR 1910.133). Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Safety Stations: Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse. Remove this material from your shoes and clean personal protective equipment.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Physical and Chemical Properties

Appearance and Odor: brown odorless gel.

Vapor Pressure: Negligible

Vapor Density (Air=1): Heavier than air.

Formula Weight: Not calculated

Specific Gravity (H₂O=1, at 4 °C): /

pH: Neutral

Water Solubility: Insoluble

Boiling Point: /

Dropping Point:265 °C

% Volatile: /

Evaporation Rate: Slower than diethyl ether

Section 10 - Stability and Reactivity

Stability: FAKKT-G133 is stable at room temperature in closed containers under normal storage and handling conditions.

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Strong oxidizing materials

Conditions to Avoid: Pyrolysis

Hazardous Decomposition Products: Thermal oxidative decomposition of FAKKT-G133 can produce carbon monoxide as well as small amounts of other toxic fumes.

Section 11- Toxicological Information

Toxicity Data: None; not considered to be a hazardous material.

Section 12 - Ecological Information

Environmental Fate and Effects: No data has been established for this product.

Section 13 - Disposal Considerations

Disposal: Contact a licensed waste-disposal contractor for detailed recommendations.

FAKKT-G133

Disposal Regulatory Requirements: Many states classify waste lubricants as “hazardous”, which means disposal only by a licensed firm. Follow applicable Federal, state, and local regulations.

Section 14 - Transport Information

DOT Transportation Data (49 CFR 172.101): Not Restricted

Section 15 - Regulatory Information

TSCA:

All components comply with TSCA.

EPA Regulations:

SARA 311/312 Codes: N/A

SARA Toxic Chemical (40 CFR 372.65): N/A

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed, Threshold Planning Quantity (TPQ): N/A

OSHA Regulations:

Air Contaminant (29 CFR 1910.1000): Oil mist in air if heated above 250°C. Limit for airborne concentration is 5mg/m³.

Section 16 - Other Information

Prepared By: GBM

Disclaimer: While the information and recommendations set forth herein are believed to be accurate as of the date hereof, HP Lubricants, Inc. makes no warranty with respect thereto and disclaims all liability with respect thereon.